



Old Town SPORTSMAN

Old Town<sup>®</sup> SPORTSMAN<sup>™</sup>

ePDL+<sup>™</sup> Display  
Replacement Kit

# SAFETY CONSIDERATIONS



## WARNING

Always have a personal flotation device and paddle with you when taking out a powered/pedal/paddle watercraft. Be especially careful when navigating in moving water, near dams, waterfalls, and/or hazardous water conditions.



## WARNING

You are responsible for the safe and prudent operation of your watercraft. We have designed your Old Town product to be an accurate and reliable tool that will enhance watercraft operation and improve your ability to catch fish. This product does not relieve you from the responsibility for safe operation of your watercraft. You must avoid hazards to navigation and always maintain a permanent watch so you can respond to situations as they develop. You must always be prepared to regain manual control of your watercraft. Learn to operate your Old Town product in an area free from hazards and obstacles.

**NOTICE:** The images in this document may not look the same as your product but your unit will function in a similar way.

# CONTENTS



## CAUTION

Before getting started, please read all instructions thoroughly to prevent injury.

**ALWAYS WEAR SAFETY GLASSES WHEN HANDLING TOOLS AND EQUIPMENT.**



### PARTS

<b>A.</b> ePDL+™ Display Assembly	<b>Part #</b> 01.1316.0226	<b>Qty</b> 1
<b>B.</b> M4 x 8 Fasteners	<b>Part #</b> 01.1316.0226	<b>Qty</b> 4

### TOOLS REQUIRED

- Safety Glasses
- 3mm Hex Key

# INSTRUCTIONS

1

## REMOVING OLD ePDL+™ DISPLAY

Begin by orienting your ePDL+™ Drive with the display facing upwards on a stable, flat working surface.



2

Using a 3mm hex key, remove the four screws on the face and top side of the display.



3

Gently lift off the existing display and unplug the BLACK display cable connector from the BLACK drive cable connector. This may be difficult to separate but PULL ONLY ON THE PLUGS.

**NOTICE:** Pull only on the plugs. Pulling on the wires may cause product damage.



4

## INSTALLING NEW ePDL+™ DISPLAY

Take the new ePDL+™ display (A) and plug the BLACK display cable connector in to the BLACK drive cable connector.

Make sure to align the arrows on each connector before pressing together firmly.



# INSTRUCTIONS

---

5

While placing the display back onto the ePDL+™ Drive, guide the excess wire into a safe location that will prevent pinching as the display is secured.



6

Locate the four new M4 x 8 fasteners (B). Hold the display in place and secure the new display onto the drive with the new fasteners using a 3mm hex key.

