

Wide One Deep

Completely waterproof, 2D view, zoom with bottom lock, Fish Id , depth alarm to 99', adjustable 3 size fish alarm,

built-in simulator, curved lens to minimize glare, quick disconnect mount fully tilting and swiveling, 2 level backlit display, never fog TM anti-fog coating.



MSRP **\$99.99**

Unit Specifications:

Display Size:	2.9" H x 2.35" W
Display Pixel Matrix:	50 X 32
Display Type:	Super Twist LCD
Operating Frequency	200 KHZ
Power Requirement	12 Volts
Depth Capability	600 Feet
Sonar Coverage:	16 Degrees

Sonar:

Target Separation:	2 1/2"
Power Output (RMS):	400 Watts
Power Output (PK to PK):	3200 Watts
Backlight:	Yes
Waterproof:	Yes
Mount:	Quick Disconnect
Unit Size:	6 3/4 " H x 6 1/4 " W x 2 14/"D
Depth	600 Feet

FACTS

Years Produced	1992
Transducer supplied	XHS 6 16
Transducer hardware	MHX HS
Connector Collector:	MBCC W2
Pub Kit w/manual	530470-1

Completely waterproof, 2D view, zoom with bottom lock, Fish ID depth alarm to 99', adjustable 3 size fish alarm,

built-in simulator, curved lens to minimize glare, quick disconnect mount fully tilting and swiveling, 2 level backlit display, never fog TM anti-fog coating.

Compatible Accessories:

Accessories pk w/unit	Part #	Standard
Transom Mount Transducer	710022-1	XHS 6 16
Optional Accessories	NA	NA
Puck Transducer	710025-1	XP 6 16
Angled Puck Transducer	710032-1	XAP 6 16
Trolling Motor Mount Transducer	710030-1	XTM 6 16
Portable Mount Transducer	710027-1	XPT 6 16
Bronze Thru Hull Transducer	710028-1	XTH 6 16
Bronze Thru Hull 3 in 1 Transducer	NA	NA
Plastic Thru Hull Transducer	710110-1	XTH 6 20 P
Mount System	740005-5	MS2 Y
Mounting Knobs	NA	NA
Temperature Sensor	NA	NA
Transducer Ext. Cable 10'	720006-6	EC 6
Transducer Ext. Cable 20'	720006-620	EC 6 20
Power Cable	720002-1	PC 10
Transducer Switch	720010-1	SS1 6
Unit Switch	720011-1	SS2 6
Unit Cover	NA	NA
Mount Cover	740036-1	MC W
Portable Conversion Kit	403720-1	PTC W2
In-Dash Mounting Kit	NA	NA
Carrying Case	780000-1	CC W